







## **ACCESSORIES**

- Strut Clamp Order to Pipe O.D.
- 16" x 18" Support pad
- Eternabond® 2-sided tape

## PRODUCT DESCRIPTION

A pipe support with "strut" used to support roof-mounted electrical conduit, solar piping, gas pipes and other mechanical piping.

Pipes rest on a 12" length of strut which is mounted on the base. The pipes can be fastened by using the appropriate pipe clamp.

## **KEY INFORMATION**

- Designed to support conduit (ganged) cable trays or other mechanical piping.
- Adjustable from the factory set maximum height of 12-7/8" down to a minimum height of 3-1/8"
- Maximum load is 186 lbs. (All-thread capacity) Make certain each support is properly elevated to evenly distribute weight at all support locations.
- Unit Weight: 8.70 lbs.
- Recommended spacing is not to exceed 10' centers depending upon the load.

## **MATERIAL INFORMATION**

- Base Material: 16 ga. 304 SS
- 1/2"-13 304 SS All-Thread
- 13/16"x1-5/8" 14 ga. HDG slotted strut
- HDG hardware

The information contained in this drawing is the sole property of MIRO Industries, Inc. Any reproduction in part or as a whole without written permission of MIRO Industries, Inc. is prohibited.

DATE: JAN 2022

8-BASE STRUT-12 SS