

Product Data Sheet

SUREFOOT ACCESS SERVICE PLATFORMS

1. **Product Name:** SUREFOOT ACCESS SERVICE PLATFORMS
2. **Manufacturer:** MIRO INDUSTRIES, INC.
844 South 430 West, Suite 100,
Heber City, Utah 84032
Phone: (800) 768-6978
Fax: (800) 440-7958
3. **Product Description:** Surefoot Access Service Platforms provide a safe and cost-effective means to access and maintain rooftop equipment. Surefoot Access Service Platforms are custom-designed to meet OSHA and building code standards for limited access applications. Service Platforms can be designed to fit around most any rooftop unit where maintenance personnel need a level and safe working service to perform their tasks, without requiring the use of a portable ladder. Access to Surefoot Access Service Platforms is typically designed to OSHA standards for standard stairways as recommended in OSHA 1910.25(b)(8). Where not feasible, an alternate method such as ship ladder or vertical ladder can also be provided where a standard stair will not work. Each service platform is designed to carry applicable loading per OSHA requirements and distribute the loading to the roof surface through the frame system connected to either a polycarbonate, stainless-steel or hot-dip galvanized base. Each Service Platform is adjustable in the field via bolted connections to accommodate roof and height variations. All metal parts are made from either hot-dip galvanized steel or stainless-steel for outdoor weathering protection. Surefoot Access Service Platforms consists of (1) a MIRO designed base with gently curved edges to protect the roof membrane that effectively distributes the weight over the maximum roof surface, (2) hot-dip galvanized steel strut or stainless-steel frame structure, and (3) galvanized planking, or bar grading with an anti-slip surface for walking on.
4. **Product Performance:** Surefoot Access Service Platforms provide a means to safely access and maintain rooftop equipment. Service Platforms are typically set on the roof surface as a free-floating system, but positive attachment of the system to the building structure may be required for code compliance. Where required, a means for positive attachment to the building structure can be provided and coordinated by MIRO Industries.
5. **Compatibility:** Surefoot Access Service Platforms are recommended for use on and are compatible with all current types of decking and with all commonly used built-up and single-ply roofing membranes where accessing rooftop equipment for inspection or service is required.
6. **Load Weight:** Maximum load weight is equivalent to and is part of the maximum roof top bearing load, which shall be determined for each platform based on dimensions and the weight of the system. MIRO recommends loading not exceed 3 lbs. per square inch from each base to the roof surface. In addition, a deflection limit for frame members shall not exceed the span length divided by 360 ($L/360$) and a maximum recommended deflection not to exceed 1/8 inch.
7. **Composition and Materials:** Service Platforms are made with either polycarbonate, hot-dip galvanized or stainless-steel bases and either hot-dip galvanized or stainless-steel framing and hardware with a non-slip plank or bar-grating as the walking surface. Base sizes are determined based on loading requirements for the support and load distribution to the roof.
8. **Size:** Surefoot Access Service Platforms are manufactured to project-specific dimensions and are to have limited-height adjustability to ensure a level surface and desired heights off the roof are achievable.
9. **Installation:** (1) Determine the required dimensions of the system including width, clearance height from the roof surface to the lowest point of the bridge section, desired elevations of the walking-working surface with respect to the roof surface and equipment to be serviced and the location of the unit on the roof, (2) assemble the Service Platform in the approximate location and make adjustments, as needed, to ensure each base rest firmly on the roof surface.

MIRO recommends an additional sheet of roofing material, or a MIRO Support Pad be installed beneath each base. For built up roofs, remove all loose aggregate from an area 2 inches larger in width and length than the base or support pad and follow the installation directions outlined above.
10. **Spacing:** Surefoot Access Service Platforms are built to standards established in OSHA 1910 Subpart D for Walking-Working Surfaces. Contractors are to ensure clearances above and around crossovers are provided in accordance with OSHA Standards.
11. **Availability:** Surefoot Access Service Platforms are marketed throughout the United States through representatives and distributors.
12. **Maintenance:** Normal maintenance is not required. Semi-annual inspection is required to check platform position, and to ensure no hazardous conditions exists on or around the system.
13. **Technical Services:** Please call MIRO INDUSTRIES, INC: (800) 768-6978 or visit our website www.miroind.com for technical information and for graphic and CAD drawing downloads.