



ACCESSORIES

- MIRO support pad
- Eternabond® 2-sided tape

PRODUCT DESCRIPTION

The MIRO Standard crossover is constructed with our patent pending J-Stringer brackets, our 16"x18" polycarbonate bases for proper load distribution, 12" non-slip planking, and 1-5/8" 12ga. strut framing.

MIRO Standard crossovers are designed to provide a set stair pitch of a 9" rise by an 11-1/2" run. The system also provides platform length adjustability in 12" increments from 48" long to 72" long.

MIRO Standard crossover structures are designed to meet OSHA 1910 Subpart D requirements for walking/working surfaces.

Anchorage of the MIRO Standard crossover to the building structure may be required for applicable lateral and uplift loading.

STANDARD-CO (INCHES)				
	A	B	C	D
MODEL NAME	CLEARANCE SPAN	CLEARANCE HEIGHT	STEP QUANTITY	TOTAL LENGTH
C-35x12	35	12-1/4	1	75-1/2
C-47x12	47	12-1/4	1	87-1/2
C-59x12	59	12-1/4	1	99-1/2
C-35x21	35	21-1/4	2	98-1/8
C-47x21	47	21-1/4	2	110-1/8
C-59x21	59	21-1/4	2	122-1/8

MIRO Standard Crossovers are shipped partially assembled. (Field assembly is required)